

Expansion/Flexible Joint Materials

NEO-FLEX 表面防火橡胶涂布系列

基材: KM600 系耐高温布
 表面 Coating: Neoprene (黑色防火橡胶)
 耐温: 150°C max.
 特性: 气密性, 耐油水耐磨,
 应用范围: 防震接头, 伸缩蛇管,
 台北市捷运系统合格之补偿器材料
 符合:
 中华民国 CNS 10285/A2 一级耐燃标准
 BS476, Part 7-1997 耐燃标准



NEO-FLEX Flame Retarded CR coated Fiberglass Cloth



NEO-Flex fabrics are designed for flexible Joints with severe vibration, flexing and Twisting with max. temperature to 130°C
 Features:

- Flame retarded
- Very resistant to oil, greases and many other petroleum products
- Excellent ozone and weather resistance

Data and Availability

产品代号 Product ID (原代号)	厚度 (mm) Thickness	单位面积重 Areal Weight (g/m ²)	颜色 Color	张力强度 Tensile Strength (N/50mm)	每卷呎吋 宽 x 长 Roll Sizes Width x Length
5-60N/N (AF406/FRN)	0.54	605	Black	3600 x 2400	1.2 x 50
12-106N/N (AF804/FRN)	1.20	1060	Black	2240 x 1800	1.2 x 50

Your Solution for Expansion Since 1989